

Fiber Wall Socket

Single or dual fiber optics

Overview

The compact fiber wall socket is designed for residential and business applications and holds up to four fiber terminations. This wall box enables the installation of either a single Sirocco Blown Tube cable using up to a 2 fiber blown unit or 2 fiber ruggedized cables to be spliced to 2 SC pigtails (PC or APC). The pigtails would which connect to adapters at the base of the unit.

This box is has a transparent plastic cover on the front adapter side, providing substantial protection to the installed fibers.

The unit can be quickly installed within an office, house or communication room environment.

Applications

- FTTx networks
- Data communication networks
- Indoor applications

Features

- SC simplex and duplex adapter
- Ergonomic design
- Ability to allow cables to enter from rear or bottom of unit
- 30mm minimum bend radius
- Flip tray to allow access to pigtails and cable entry
- Removable cover for easy access
- Manufactured from fire resistant UL94-Vo rated material
- Standard white color



Technical Specifications

Parameters	Specifications
Height	86mm
Width	86mm
Depth	25mm
Number of Ports	1 or 2
Mac. Splicing Capacity	2 Splices
Suitable Adaptor Type	SC simplex, SC Duplex
Number of Cable Entry	2
Material	PC+ABS
Operating Temperature	-40°C ~ +50°C
Color	White
Complaint to	RoHS, REACH/SvHC