

# OD-WB1224L

## Fiber Optic In/Outdoor Lockable Wall Box

### Overview

The OD-WB1224L Lockable IP65 distribution box offers the ability to terminate 24 fibers in a strong robust ABS enclosure for indoor and outdoor applications. An internal detachable tray provides a neat solution for housing 24 SC simplex connections and splices.

The box has 24 patch cord exitpoints and up to 2 cable entry points which maintain the IP65 rating. Integrated cable tie points are included to secure incoming cables. A lock feature adds extra security when positioned in un-secure areas.

### Applications

Data center, premise installations, telecommunication networks Ethernet, Fiber channel, ATM, LAN, MAN and WAN Data communication and telecommunication networks Indoor/outdoor applications.

### Features

- IP65 rating for external use
- Lockable door for added security
- Integrated cable tie points for securing incoming cable
- Up to 24 splice & SC connection points
- Removable splice tray for easy installation
- Accepts loose tube, distribution and pre-terminated cables
- Integrated bend radius protection
- Sealing glands for up to 24 exiting cables + 2 incoming cable
- Removable door for ease of installation
- Supplied with 24 heatshrink splice protectors
- Supplied with transit tubing
- Supplied with wall fixing and tie weaps
- RoHS, REACH & SvHC compliant



Closed View



Open View

### Technical Specifications

Parameters	Specifications
Height	<b>24 ~ 96F</b> 340mm
Weight	270mm
Depth	110mm
Net weight	1.8kg
IP rating	IP65
Suitable for adaptor type	SC simplex
Number of ports	24
Cable entry	2
Material	ABS
Color	Grey Ray 7305
Operating Temperature	-40°C ~ +60°C
Complaint to	RoHS, REACH/SvHC