

# ODTray1222

## Fiber Optic Inline Enclosure

### Overview

The ODTray1222 inline enclosure is a horizontal type with a hinge on one side and an opening on the other side. Two insert plates, with fixing bolts, are used to fix and seal inline enclosure.

The ODTray1222 inline enclosure has our advanced formula, company patent elastic seal fitting, our fitting is made of injection-molded, high quality elastic material via numerical control equipment. It is installed between the enclosure housing and the insert plates.



Closed View



Open View

### Technical Specifications

Items	Specifications	
	24 ~ 96F	144 ~ 192F
Number of inlet/outlet ports	6 ports (3 each side)	6 ports (3 each side)
Suitable cable jacket diameter	Ø8 ~ 16(mm)	Ø8 ~ 23(mm)
Maximum capacity (F)	Bunchy: 6 ~ 96 (Cores) Ribbon: Max. 144 (Cores)	Bunchy: 12 ~ 192 (Cores) Ribbon: Max. 432 (Cores)
Single piece package size	460x220x120(mm)	460x220x170(mm)
Single piece package weight	2.9kg ~ 3.5kg	3.3kg ~ 3.6kg
Group package size	630x470x470(mm)	470x450x450(mm)
Group package quantity	10pcs/carton	6pcs/carton